

## KS 55 (600855000) Circular Saw

## **Cardboard box**

Order no. 600855000 EAN 4007430230409



Product may differ from Image

- Light, compact circular saw for universal construction site use
- Grip area with non-slip soft-grip surface
- Clearly visible cutting indicator for precise sawing after initial cut
- 0° position re-adjustable for highest cutting precision
- Extraction possibility by means of connecting an all-purpose vacuum cleaner

Technical data	
Characteristics	
Rated input power	1200 W
Output power	670 W
Maximum cutting depth at 90°	55 mm / 2 5/32 "
Maximum cutting depth at 45°	39 mm / 1 17/32 "
Saw blade Ø x bore	160 x 20 mm / 6 1/4 x 0.787 "
Swivel range from / to:	0 / + 47 °
No-load speed	5600 rpm
Revolutions at rated load	4400 rpm
Max. cutting speed	47 m/s / 154 ft/s
Torque	5 Nm / 44 in-lbs
Weight (without power cable)	4 kg / 8.8 lbs
Cable length	4 m / 13 ft

www.metabo.com 1 / 2



## Vibration

Sawing chipboards	3.4 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s²
Noise emission	
Sound pressure level	93 dB(A)
Sound power level (LwA)	104 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Carbide circular saw blade (18 teeth)

Hexagonal wrench

Parallel guide / rip fence

Extraction connector

www.metabo.com 2 / 2