

DECLARATION OF PERFORMANCE

According to Annex III of the Regulation (EU) Nr. 305/2011 (Construction Products Regulation)

Festool Drywall Fastening Screws DWS C

- 1 **Unique identification code of the product-type:** Festool Drywall Fastening Screws DWS C
- 2 **Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to article 11(4):** Type and Lot-Number displayed on the packaging
- 3 **Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:**

Generic type and use	Fastening screws for gypsum plasterboards
Product size covered	3.9 mm thread diameter
Fastened material and base	DWS C FT (fine thread): Gypsum plasterboards to metal profile of steel grade \geq S235; metal profile thickness \leq 0.7 mm DWS C CT (course thread): Gypsum plasterboards to wood substructure
Fastener head type	Flat trumpet head
Fastener thread type	DWS C FT: fine thread; DWS C CT: course thread
Fastener material, coatings	Black phosphated

- 4 **Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to article 11(5):** Festool Group GmbH & Co. KG, Wertstraße 20, D-73240 Wendlingen, Germany
- 5 **Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in article 12(2):** n. a.
- 6 **System or systems of assessment and verification of constancy of performance of the construction product as set out in annex V:** System 4
- 7 **In case of the declaration of performance concerning a construction product covered by a harmonized standard:** No third party tasks according to EN 14566:2009-10 required
- 8 **In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:** n. a.
- 9 **Declared performance:**

Essential Characteristic	Performance	Harmonized Technical Specification
Flexural strength	Pass	EN 14566:2009-10
Release of dangerous substances	Pass	
Withdrawal force	Pass	
Corrosion resistance	\geq 48 hours salt spray test	
Surface hardness	\geq 55 HRC	
Reaction to fire	Clas A1, no contribution to fire	

- 10 **The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.**

Signed for and on behalf of the manufacturer by:



Wendlingen, den 01. 07. 2013

Dr. M. Zimmer
Manager R & D